

# PRODUCT DATASHEET

## STERIWHITE AIRQ600 R

STERIWHITE AIRQ600 | UVC disinfection of ambient air in rooms with constant occupancy



---

### Product features

- Extremely quiet, no annoying air flow
- Energy-efficient
- Low-maintenance
- Easy operation
- Modern design
- One performance level 600 m<sup>3</sup>/h at <39 dB (A)
- Made in Germany

TECHNICAL DATA

Electrical data

Nominal wattage	300.00 W
Nominal voltage	230 V
Mains frequency	50 Hz
Protection class	I
Operating mode	Integrated driver


UV & Air cleaning

Maximum disinfection volume flow	600 m³/h
Air circulation	600 m³/h
UV radiated power	204 W
UV-C source lifetime	16000 h
Noise level in UV-C disinfection mode	< 39 dB
Suitable for room space up to	70 m²

Dimensions & Weight

Length	315.00 mm <sup>1)</sup>
Width	860.00 mm <sup>1)</sup>
Height	860.00 mm <sup>1)</sup>
Product weight	53000.00 g
Cable length	3000 mm

1) The dimension can vary depending on type of mounting variant



STERIWHITE AIRQ600 R /  
STERIWHITE AIRQ600 W

Materials & Colors

Product color	White
---------------	-------

Body material	Steel
Mercury content	0.0 mg


### Application & Mounting

Ambient temperature range	0...+40 °C
Type of connection	Plug type C (EU)
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Standing
Mounting location	Floor

### Certificates & Standards

Standards	CE
-----------	----

### DOWNLOAD DATA

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4260732190042	Shipping box 1	1,200 mm x 800 mm x 1,500 mm	80000.00 g	1440.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.