

PRODUCT DATASHEET

LDVAL FL 100W 865

LED VALUE FLOODLIGHT GEN3 | Floodlights



Areas of application

- Architectural lighting
- Security lighting
- Public areas

Product benefits

- Low windage thanks to the compact and slim design
- Breather protects luminaires against the siphonage
- Texture glass offer a comfortable lighting
- IP65 protection is suitable for outdoor application

Product features

- Lifetime up to 30,000 h
- Available in 10 W, 20 W, 30 W, 50 W, 100 W, 150 W and 200 W
- Power factor: > 0.9
- Safety compliance certificates: CB, EMC, RoHS 2.0
- Driver on board technology platform
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index R_a : > 80

TECHNICAL DATA

Electrical data

| | |
|---|-----------------------|
| Nominal wattage | 100.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 477.000 mA |
| Inrush current | 20 A |
| Max. number of luminaires per miniature circuit breaker B16 | - |
| Max. number of luminaires per miniature circuit breaker C16 | - |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | I |
| Operating mode | Integrated LED driver |

Photometrical data

| | |
|--|----------|
| Luminous flux | 10000 lm |
| Luminous efficacy | 100 lm/W |
| Color temperature | 6500 K |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 5 sdcm |
| Luminous intensity | 3660 cd |
| Flickering metric (Pst LM) | - |
| Stroboscope effect metric (SVM) | - |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 255.00 mm |
| Width | 236.00 mm |
| Height | 40.00 mm |
| Product weight | 1250.00 g |
| Cable length | 500 mm |

LDVAL FL 100W

Materials & Colors

| | |
|--|----------|
| Product color | Black |
| Housing color | Black |
| Body material | Aluminum |
| Cover material | Glass |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|--------------|
| Ambient temperature range | -30...+50 °C |
| Temperature range at storage | -40...+70 °C |
| Type of protection | IP65 |
| Protection class IK (shock resistance) | IK06 |
| Dimmable | No |
| Mounting type | Surface |
| Replaceable light source | No |

Lifespan


| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
| Lifespan L80/B10 at 25 °C | 24000 h ¹⁾ |
| Lifespan L80/B50 at 25 °C | 24000 h |
| Lifespan L90/B10 at 25 °C | 18000 h |
| Number of switching cycles | 30000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| | |
|----------------------------------|-----------------|
| Standards | CB / RoHS / EMC |
| Replaceable light source (EPREL) | Not replaceable |

DOWNLOAD DATA

| Photometric and lighting design files | | Document name |
|--|----------------|-------------------|
|  | IES file (IES) | LDVAL FL 100W 865 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075589278 | Folding box 1 | 75 mm x 299 mm x 272 mm | 1985.00 g | 6.10 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075589285 | Shipping box 2 | 311 mm x 164 mm x 292 mm | 4223.00 g | 14.89 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.