

PRODUCT DATASHEET LED CCT SELECTABLE CLAS A 60 8 W/2700 K / 4000 K / 6500 K B22d

LED CCT selectable lamp | Three color in one lamp, classic bulb shape and stick shape



Areas of application

- Dining table lighting
- Ceiling lights
- Indoor applications
- Domestic applications
- General illumination

Product benefits

- Reliable operation thanks to brand quality
- Color change by double click existing switch

Product features

- Three color in one lamp: 827, 840 and 865
- No need re-wiring
- No internet is required
- Long lifetime up to 15,000 h
- Overtemperature protection



tháng 8 02, 2025, 05:52:11 LED CCT SELECTABLE CLAS A 60 8 W/2700 K / 4000 K / 6500 K B22d - Input voltage: 220...240 V_{AC}

TECHNICAL DATA

Electrical data

| Nominal wattage | 8 W |
|--|----------|
| Construction wattage | 8.00 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 60 W |
| Nominal current | 69 mA |
| Type of current | AC |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Power factor λ | 0.50 |

Photometrical data

| Luminous flux | 806 lm | |
|---|------------------------------------|--|
| Luminous efficacy | 93 lm/W / 106 lm/W / 100 lm/W | |
| Lumen main.fact.at end of nom.life time | 0.70 | |
| Light color (designation) | Warm White / Cool White / Daylight | |
| Color temperature | 2700 K / 4000 K / 6500 K | |
| Color rendering index Ra | 80 | |
| Light color | 827/840/865 | |
| Standard deviation of color matching | ≤6 sdcm | |

Light technical data

| Beam angle | 200 ° |
|---------------|---------|
| Starting time | < 0.5 s |

Dimensions & Weight

| Overall length | 107.00 mm |
|------------------|-----------|
| Diameter | 60.00 mm |
| Maximum diameter | 60 mm |
| Product weight | 26.00 g |

Temperatures & operating conditions

Lifespan

| Number of switching cycles | 100000 |
|---|-----------------|
| | 100000 |
| Additional product data | |
| Base (standard designation) | B22d |
| Mercury content | 0.0 mg |
| Capabilities | |
| Dimmable | No |
| Certificates & Standards | |
| Type of protection | IP20 |
| Photobiological safety group acc. to EN62778 | RGO |
| Country-specific categorizations | |
| Order reference | LSCLA608W/827/8 |
| LOGISTICAL DATA | |
| Temperature range at storage | -20+80 °C |
| Energy labelling regulation data acc EU 2019/2015 | |
| Light source cap-type (or other electric interface) | B22d |
| Length | 107.00 mm |
| Height | 60.00 mm |

LOGISTICAL DATA

Width

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075727267 | Folding box 1 | 62 mm x 62 mm x 115 mm | 40.00 g | 0.44 dm ³ |
| 4058075727274 | Shipping box 10 | 312 mm x 129 mm x 129 mm | 445.00 g | 5.19 dm ³ |

60.00 mm

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.