

# PRODUCT DATASHEET LVED VAL 6,5/220-240/120

## Constant current LED drivers | Constant currect LED drivers



#### Areas of application

- Suitable for indoor lights
- Suitable for shops/Supermarket/Hotel/offices/residential etc. applications

#### **Product benefits**

- Long lifetime to reduce the maintenance cost
- High Power factor
- Low ripple current with flicker free
- Various currents-wattages for wide application setting, more flexibility
- SELV system
- Compact housing

#### **Product features**

- IP20 Constant current LED driver
- Wattage: 6.5W/8W/8.4W/10.5W/12.6W/17.5W/21W/29.4W/33.6W/37.8W/40.4W
- Currents: 120/150/200/250/300/350/500/700/800/900/1050mA
- Frequency: 50/60Hz
- Long lifetime up to 50k hrs@tc max
- SELV and suitable for independent application
- Class II

#### **TECHNICAL DATA**

### Electrical data

Nominal wattage	6.50 W
Nominal voltage	220240 V
Nominal output voltage	2754 V
Nominal output current	120 mA
Mains frequency	50/60 Hz
Power factor $\lambda$	0.95 <sup>1)</sup>
Galvanic isolation	SELV

1) At full load

## **Dimensions & Weight**

Length	100.00 mm
Width	38.00 mm
Height	25.00 mm
Product weight	44.00 g

### Colors & materials

Product color	White/Orange
Body material	Plastic

## Temperatures & operating conditions

Ambient temperature range	-20+45 °C
---------------------------	-----------

## Capabilities

Dimmable
----------

## **Certificates & Standards**

Approval marks – approval	СВ
Protection class	II
Type of protection	IP20

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854000720	Unpacked 1			
4099854000737	Shipping box 60	331 mm x 185 mm x 228 mm	2940.00 g	13.96 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.