

PRODUCT DATASHEET LED VALUE SOLAR FLOODLIGHT LA 300 730

LED VALUE SOLAR FLOODLIGHT | Floodlights



Areas of application

- Security lighting
- Amenity and parking area lighting
- Residential sector
- Architectural lighting
- Landscape lighting

Product benefits

- Die-cast aluminum housing ensures reliable operation
- High system efficacy up to 190 lm/W leads to energy savings
- 12 hours lighting per night to fulfill the whole night application
- Lamp body and solar panel split design, easy for charging and lighting
- Professional lighting distribution provides uniformity lighting

Product features

- Available in 3 lumen packages (3 sizes)
- LiFeP04 battery charge-discharge cycle 2000 times
- Battery overcharge, overdischarge, overheat and short circuit protections
- Grade A monocrystalline solar panel
- UV stabilized polycarbonate lens
- Remote control provided for easy control of operation
- Type of protection: IP66
- Impact resistance: IK08

TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Protection class	Ш

Photometrical data

Luminous flux	2900 lm
Luminous efficacy	160 lm/W
Color temperature	3000 K

Dimensions & Weight

Length	350.00 mm
Width	530.00 mm
Height	17.00 mm
Product weight	3630.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP66
Dimmable	Yes
Mounting type	Surface
Application environment	Outdoor
Replaceable light source	No

BATTERY

Ī	Battery size [GMS]	Others
	Battery Size [GIVIS]	Others

Certificates & Standards

Replaceable light source (EPREL) Not replaceable	Replaceable light source (EPREL)	Not replaceable	
---	----------------------------------	-----------------	--

DOWNLOAD DATA

Photometric and lighting design files		Document name	
	IES file (IES)	LDVAL SOLAR FL LA 300 730	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854005534	Folding box 1	367 mm x 47 mm x 547 mm	3815.00 g	9.44 dm ³
4099854005541	Shipping box 5	567 mm x 252 mm x 385 mm	20575.00 g	55.01 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.