

PRODUCT DATASHEET

IP65 BULKHEAD 15W 830 WT OV

IP65 BULKHEAD | Stylish and contemporary designed luminaire, suitable for all outdoor applications



Areas of application

- Public areas
- Gardens
- Pathway lighting
- Outdoor applications
- Corridors, stairways, entrance areas
- Passages, underpasses

Product benefits

- Stylish and modern design

Product features

- Color temperature: 3,000 K, 4,000 K, 6,500 K
- High luminous efficacy: 90 lm/W
- Available in 15W, 20W, 24W
- Type of protection: IP65
- Impact resistance: IK06
- Available in round and oval form
- Color: black or white
- Polypropylene housing
- Lifetime up to 25,000 h

TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 15.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Power factor λ | > 0.90 |
| Protection class | II |

Photometrical data

| | |
|--|---------|
| Luminous flux | 1200 lm |
| Total luminous flux of contained light sources | 1350 lm |
| Luminous efficacy | 80 lm/W |
| Color temperature | 3000 K |
| Color rendering index Ra | > 80 |
| Beam angle | 120 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 200.00 mm |
| Width | 100.00 mm |
| Height | 45.00 mm |
| Product weight | 157.00 g |

LDECO BH

Materials & Colors

| | |
|-----------------|--------------------|
| Product color | White |
| Housing color | White |
| Body material | Plastic |
| Cover material | Polypropylene (PP) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+45 °C |
| Type of protection | IP65 |
| Dimmable | No |
| Mounting type | Surface |

| | |
|--------------------------|---------|
| Application environment | Outdoor |
| Replaceable light source | No |

Certificates & Standards

| | |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854098796 | Folding box 1 | 100 mm x 48 mm x 205 mm | 211.00 g | 0.98 dm ³ |
| 4099854098802 | Shipping box 20 | 510 mm x 220 mm x 225 mm | 4850.00 g | 25.25 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.