

PRODUCT DATASHEET LED PERFORMANCE DP 1200 14W 865

Standard ON-OFF version | Damp-proof luminaires



Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines
- Warehouses, logistic halls
- Humid and dirty application areas

Product benefits

- UV-stabilized polycarbonate opal diffuser for uniform light distribution and long durability
- Polycarbonate body and diffuser offers IK08 impact protection
- Sleek and lightweight slim body design, compact but powerful
- Long 50,000 hours lifetime reduces maintenance costs

Product features

- Available in 7 wattages and lumen packages
- Available in 3 length options, ensuring direct replacement of traditional 2-4-5 feet fluorescent dampproof fixtures
- High system lumen efficacy: up to 150 lm/W
- Color rendering index Ra: > 80
- Four versions: standard on-off, wide voltage on-off, Tri-CCT and DALI DIM
- Anti-corrosion stainless steel clips
- Type of protection: IP66
- Impact resistance: IK08
- Certificate: CB, EMC, RoHS
- Class I Luminaires

TECHNICAL DATA

Electrical data

Nominal wattage	14.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1

Photometrical data

Luminous flux	2100 lm
Luminous efficacy	150 lm/W
Color temperature	6500 K
Color rendering index Ra	> 80
Beam angle	120°

Dimensions & Weight

Length	1199.00 mm
Width	77.00 mm
Height	68.00 mm
Product weight	1280.00 g



LDPFM DP 1200 G4

Materials & Colors

Body material

Application & Mounting		
Type of protection	IP66	
Dimmable	No	
Mounting type	Surface	
Replaceable light source	No	

Plastic

Certificates & Standards

Replaceable light source (EPREL) Not replaceable

DOWNLOAD DATA

	Documents and certificates	Document name	
User instruction / safety instructions		LDPFM DP 600_1200_1500_G4 UI	
	Photometric and lighting design files	Document name	

Photometric and lighting design files Document name	
IES file (IES)	LDPFM DP 1200 14W 865 G4 LEDV

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854138126	Folding box 1	72 mm x 82 mm x 1,205 mm	1304.00 g	7.11 dm ³
4099854138133	Shipping box 6	1,221 mm x 163 mm x 276 mm	8554.00 g	54.93 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.