

# PRODUCT DATASHEET LED PERFORMANCE DP 1500 57W 840

# Standard ON-OFF version | Damp-proof luminaires



#### Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines
- Warehouses, logistic halls
- Humid and dirty application areas

#### Product benefits

- UV-stabilized polycarbonate opal diffuser for uniform light distribution and long durability
- Polycarbonate body and diffuser offers IK08 impact protection
- Sleek and lightweight slim body design, compact but powerful
- Long 50,000 hours lifetime reduces maintenance costs

#### Product features

- Available in 7 wattages and lumen packages
- Available in 3 length options, ensuring direct replacement of traditional 2-4-5 feet fluorescent dampproof fixtures
- High system lumen efficacy: up to 150 lm/W
- Color rendering index Ra: > 80
- Four versions: standard on-off, wide voltage on-off, Tri-CCT and DALI DIM
- Anti-corrosion stainless steel clips
- Type of protection: IP66
- Impact resistance: IK08
- Certificate: CB, EMC, RoHS
- Class I Luminaires

# **TECHNICAL DATA**

#### Electrical data

Nominal wattage	57.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	I

#### Photometrical data

Luminous flux	8550 lm
Luminous efficacy	150 lm/W
Color temperature	4000 K
Color rendering index Ra	> 80
Beam angle	120 °

# Dimensions & Weight

Length	1499.00 mm
Width	77.00 mm
Height	68.00 mm
Product weight	1550.00 g



LDPFM DP 1500 G4

# Materials & Colors

Body material

Application & Mounting			
Type of protection	IP66		
Dimmable	No		
Mounting type	Surface		
Replaceable light source	No		

Plastic

# Certificates & Standards

Replaceable light source (EPREL)	Not replaceable

# DOWNLOAD DATA

Documents and certificates Do		Document name	Document name	
POF	User instruction / safety instructions	LDPFM DP 600_1200_1500_G4 UI		
	Photometric and lighting design files	Document name		

LDPFM DP 1500 57W 840 G4 LEDV

# LOGISTICAL DATA

IES file (IES)

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854138263	Folding box	72 mm x 82 mm x 1,505 mm	1574.00 g	8.89 dm <sup>3</sup>
4099854138270	Shipping box 6	1,521 mm x 163 mm x 276 mm	10332.00 g	68.43 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.