

PRODUCT DATASHEET

LED ECO LITE DAMP PROOF HOUSING DE G2 1200

LED ECO LITE DAMPPROOF HOUSING G2 | Damp-proof housing with back-plate



Areas of application

- Industrial and storage facilities
- Car parks
- Garages
- Workshops, assembly lines

Product benefits

- UV stabilized, impact resistant polycarbonate diffuser and body
- VDE certified components ensure product reliability

Product features

- Lifetime up to 25,000 h
- Protection class: I
- Protection rating: IP65
- Classic design with PC body and PC diffuser
- Back-plate to cover wires

TECHNICAL DATA

Electrical data

| | |
|------------------|-------------|
| Nominal voltage | 100...277 V |
| Mains frequency | 50...60 Hz |
| Protection class | I |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1277.00 mm |
| Width | 109.00 mm |
| Height | 67.00 mm |
| Product weight | 1265.00 g |



LED ECO LITE DP HOUSING


Materials & Colors

| | |
|---------------|--------------------|
| Product color | Gray |
| Housing color | Gray |
| Body material | Polycarbonate (PC) |

Application & Mounting

| | |
|---------------------------|-------------------|
| Ambient temperature range | -20...+45 °C |
| Type of protection | IP65 |
| Dimmable | No |
| Mounting type | Surface/Suspended |
| Application environment | Indoor |
| Replaceable light source | No |

DOWNLOAD DATA

| Documents and certificates | Document name |
|---------------------------------------------------------------------------------------------------------------------------|-----------------------------|
|  User instruction / safety instructions | LDECOLITE DP DE LAMPHOUSING |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854514098 | Folding box 1 | 112 mm x 69 mm x 1,279 mm | 1333.00 g | 9.88 dm ³ |
| 4099854514104 | Shipping box 8 | 1,300 mm x 240 mm x 305 mm | 11742.00 g | 95.16 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.