

## PRODUCT DATASHEET

### LED VALUE CLASS A 6.5 W/3000 K E27 GEN4

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### Product features

- Color rendering index  $R_a \geq 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Nominal wattage	6.5 W
Construction wattage	6.50 W
Nominal voltage	100...240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	70 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	> 0.70

### Photometrical data

Luminous flux	806 lm
Nominal useful luminous flux 90°	806 lm
Luminous efficacy	124 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Standard deviation of color matching	≤6 sdcn

### Light technical data

Beam angle	180 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	108.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	35.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

#### Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

#### Capabilities

Dimmable	No
----------	----

#### Certificates & Standards

Energy efficiency class	A++ <sup>1)</sup>
Photobiological safety group acc. to EN62778	RG1

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

#### Country-specific categorizations

Order reference	LVCLA606.5W/830
-----------------	-----------------

#### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	108.00 mm
Height	60.00 mm
Width	60.00 mm

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075282186	Folding box 1	61 mm x 61 mm x 115 mm	51.00 g	0.43 dm <sup>3</sup>
4058075282193	Shipping box 10	322 mm x 136 mm x 135 mm	637.00 g	5.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.