

# PRODUCT DATASHEET LED VALUE CLAS P 4.7 W/2700 K E14

LED VALUE CLASSIC P | LED lamps, classic mini-ball shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### Product features

- Color rendering index Ra: ≥ 80
- Not dimmable
- Mercury-free lamps



# TECHNICAL DATA

# Electrical data

Nominal wattage	4.7 W
Construction wattage	4.70 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	43 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

## Photometrical data

Luminous flux	470 lm
Luminous efficacy	100 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	180 °
Starting time	≤ 0.5 s

# Dimensions & Weight

Overall length	79.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	15.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C

# Lifespan

Lifespan L70/B50 at 25 °C	15000 h
---------------------------	---------

	PRODUC	IDATASHEET	
Number of switching cycles	100000		
Additional product data			
Base (standard designation)	E14		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Capabilities			
Dimmable	No		
Certificates & Standards			
Type of protection	IP20		
Standards	CB / EMC / SAA / ROHS		

## Country-specific categorizations

Photobiological safety group acc. to EN62778

Order reference	LVCLP40 4,7W/82
	LVGLP40 4,7W/82

RG0

### LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Light source cap-type (or other electric interface)	E14
Length	79.00 mm
Height	45.00 mm
Width	45.00 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854310386	Folding box 1	45 mm x 45 mm x 84 mm	24.00 g	0.17 dm <sup>3</sup>
4099854310393	Shipping box 10	233 mm x 98 mm x 96 mm	301.00 g	2.19 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.