

PRODUCT DATASHEET LED VALUE CLAS B FIL 4 W/2700 K B15d FR GEN2

LED VALUE CLASSIC B FILAMENT | LED lamps, classic mini-candle shape



Areas of application

- Decorative applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower thermal output (compared with the standard reference product)
- Can be easily fitted instead of ordinary light bulbs

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Good quality of light; color rendering index R_a: ≥ 80; constant chromaticity
- Lifetime up to 15,000 h



FR GEN2

TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	36 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.4

Photometrical data

Luminous flux	470 lm
Luminous efficacy	117 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827

Light technical data

Beam angle	300 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	98.00 mm
Diameter	45.00 mm
Product weight	16.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
3	

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	B15d

Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable		No
----------	--	----

Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	LV CLB 4W/827 2

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B15d
Length	98.00 mm
Height	45.00 mm
Width	45.00 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	AC14560 LED VALUE CLB 4W GLFR 2700K G2AU
LDT file (Eulumdat)	LED VALUE CLAS B FIL 4 W 2700K B15d FR GEN2
Light distribution curve type polar	LED VALUE CLAS B FIL 4 W 2700K B15d FR GEN2

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267664	Folding box 1	51 mm x 51 mm x 130 mm	28.00 g	0.34 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854260032	Shipping box 10	266 mm x 109 mm x 142 mm	425.00 g	4.12 dm ³
4058075506473	Shipping box 10	266 mm x 109 mm x 142 mm	425.00 g	4.12 dm ³
4058075267671	Shipping box 10	266 mm x 109 mm x 142 mm	414.00 g	4.12 dm ³
4058075750838	Shipping box 10	266 mm x 109 mm x 142 mm	424.00 g	4.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.