

PRODUCT DATASHEET ST LINE 78.00 mm 75 8 W/2700 K R7s

LED STAR LINE R7s | Double-ended special LED lamps



Areas of application

- Hospitality
- Domestic applications
- Outdoor applications only in suitable luminaires

Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Three year guarantee
- Good all-around light emission
- Fits into most R7s luminaires thanks to excentric base

Product features

- LED alternative to conventional R7s lamps





TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	69 mA
Type of current	AC
Inrush current	4,68 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	71
Max. lamp number on MCB B16 A	114
Power factor λ	0.50


Photometrical data

Luminous flux	1055 lm
Nominal useful luminous flux 90°	1055 lm
Luminous efficacy	131 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	78.00 mm
Diameter	29 mm
Maximum diameter	29 mm
Product weight	51.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	90 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	8.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

tháng 11 22, 2025, 13:56:37 ST LINE 78.00 mm 75 8 W/2700 K R7s

ILCOS	DRDG-8/827-230-R7s-114,2
Order reference	LEDSLI 78 75 8W

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	R7s
Correlated colour temperature type	SINGLE_VALUE
Length	78.00 mm
Height	29 mm
Width	29 mm
EPREL ID	1402933

Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	R7S lamp AC11922

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075811676	Blister 1	37 mm x 140 mm x 120 mm	63.00 g	0.62 dm ³
4058075272170	Folding box 1	30 mm x 30 mm x 82 mm	54.00 g	0.07 dm ³
4058075811683	Shipping box 9	345 mm x 153 mm x 136 mm	722.00 g	7.18 dm³
4058075272187	Shipping box 10	169 mm x 72 mm x 91 mm	571.00 g	1.11 dm ³
4058075272194	Shipping box 120	347 mm x 226 mm x 191 mm	7035.00 g	14.98 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.osram-lamps.com/led-lamps

- For Guarantee see www.osram-lamps.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.