

PRODUCT DATASHEET ST LINE 118.00 mm 125 15 W/2700 K R7s

LED STAR LINE R7s | Double-ended special LED lamps



Areas of application

- Hospitality
- Domestic applications
- Outdoor applications only in suitable luminaires

Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Three year guarantee
- Good all-around light emission
- Fits into most R7s luminaires thanks to excentric base

Product features

- LED alternative to conventional R7s lamps





TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	125 W
Nominal current	125 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	41
Max. lamp number on MCB B16 A	66
Power factor λ	0.50


Photometrical data

Nominal useful luminous flux 90° 2000 lm Luminous efficacy 133 lm/W Lumen main.fact.at end of nom.life time 0.70 Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Standard deviation of color matching ≤6 sdcm Rated LLMF at 6,000 h 0.80	Luminous flux	2000 lm
Lumen main.fact.at end of nom.life time 0.70 Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Standard deviation of color matching ≤6 sdcm	Nominal useful luminous flux 90°	2000 lm
Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Standard deviation of color matching ≤6 sdcm	Luminous efficacy	133 lm/W
Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Standard deviation of color matching ≤6 sdcm	Lumen main.fact.at end of nom.life time	0.70
Color rendering index Ra ≥80 Light color 827 Standard deviation of color matching ≤6 sdcm	Light color (designation)	Warm White
Light color 827 Standard deviation of color matching ≤6 sdcm	Color temperature	2700 K
Standard deviation of color matching ≤6 sdcm	Color rendering index Ra	≥80
	Light color	827
Rated LLMF at 6,000 h 0.80	Standard deviation of color matching	≤6 sdcm
	Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	118.00 mm
Diameter	29.00 mm
Maximum diameter	29 mm
Product weight	92.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	98 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	15.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

ILCOS	DRDG-15/827-230-R7s-114,2
Order reference	LEDSLI118125 15

Energy labelling regulation data acc EU 2019/2015

R7s
SINGLE_VALUE
118.00 mm
29.00 mm
29.00 mm
1402934
AC11923

Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	EC declaration R7S lamp AC11923

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075811614	Blister 1	37 mm x 140 mm x 120 mm	104.00 g	0.62 dm ³
4058075811621	Shipping box	345 mm x 153 mm x 136 mm	1075.00 g	7.18 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.osram-lamps.com/led-lamps
- For Guarantee see www.osram-lamps.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

R7s