

# PRODUCT DATASHEET HALOLINE 300 W 220...240 V R7S

HALOLINE® Standard | Double ended halogen lamps with tube base



#### Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

#### Product benefits

- Brilliant accent light
- No transformer required
- Contains no mercury

#### **Product features**

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R<sub>a</sub>: 100
- Color temperature: 3,000 K
- Burning position: p15

## TECHNICAL DATA

#### Electrical data

| Nominal wattage      | 300 W    |
|----------------------|----------|
| Construction wattage | 300.00 W |
| Nominal voltage      | 220240 V |

## Photometrical data

| Luminous flux             | 4400 lm    |
|---------------------------|------------|
| Luminous efficacy         | 14 lm/W    |
| Light color (designation) | Warm White |
| Color temperature         | 2900 K     |
| Color rendering index Ra  | 100        |
| Light color               | 1029       |
| UV protection             | No         |

#### Light technical data

| Starting time | 0 s |
|---------------|-----|
|---------------|-----|

#### **Dimensions & Weight**

| Overall length | 119.60 mm |
|----------------|-----------|
| Diameter       | 12.00 mm  |
| Product weight | 7.00 g    |

## Additional product data

| Base (standard designation) | R7s   |
|-----------------------------|---|
| Mercury-free                | Yes   |
| Design / version            | Tube  |
| Product remark              | Fuse protection with indicated values recommended acc. to<br>IEC60357, EN60357 / Banned from 1.9.2009 as per EU phase-out<br>plan |

# Capabilities

| Dimmable         | Yes |
|------------------|-----|
| Burning position | Any |

# Country-specific categorizations

| ILCOS           | HDG-300-220/240-R7s-114,2 |
|-----------------|---------------------------|
| Order reference | 64705 300W 220-           |

## Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | R7s |
|---|-----|
|---|-----|

| Length | 119.60 mm |
|--------|-----------|
| Height | 12.00 mm  |
| Width  | 12.00 mm  |

#### Safety advice

- Do not touch the lamp if broken.

- Must not be used if outer bulb is defective.

- Lamp to be used only in a closed luminaire.

- Not designed as a replacement for conventional lighting in private household.

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300824642 | Blister<br>1                 | 185 mm x 89 mm x 12 mm               | 12.00 g      | 0.20 dm <sup>3</sup> |
| 4050300824659 | Shipping box<br>20           | 247 mm x 94 mm x 199 mm              | 358.00 g     | 4.62 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.