

PRODUCT DATASHEET

DST STICK 20 W/860 B22D

OSRAM DULUXSTAR® COMPACT | CFLi, stick shape, with screw base



TECHNICAL DATA

Electrical data

Nominal wattage	20 W
Construction wattage	20.00 W
Nominal voltage	220...240 V
Nominal current	200 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

Photometrical data

Luminous flux	1180 lm
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865

Dimensions & Weight

Overall length	159.00 mm
Diameter	48,0 mm
Product weight	85.00 g

Additional product data

Base (standard designation)	B22d
Mercury content	1.8 mg
Mercury-free	No

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

ILCOS	FBT-20/60/1B-220/240-B22D
Order reference	DSTAR 20W/865 2

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	159.00 mm
Height	48,0 mm
Width	48,0 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300926445	Folding box 1	49 mm x 49 mm x 156 mm	118.00 g	0.37 dm ³
4008321873569	Shipping box 20	268 mm x 216 mm x 179 mm	2209.00 g	10.36 dm ³
4058075011199	Shipping box 20	262 mm x 209 mm x 179 mm	2155.00 g	9.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.