

PRODUCT DATASHEET

DST STICK 23 W/865 220...240 V E27

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

Product benefits

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h




TECHNICAL DATA

Electrical data

Nominal wattage	23 W
Construction wattage	23.00 W
Nominal voltage	220...240 V
Nominal current	230 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

Photometrical data

Luminous flux	1380 lm
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865



349641_FL_865

Dimensions & Weight

Overall length	176.00 mm
Diameter	52,0 mm
Product weight	85.00 g

Additional product data

Base (standard designation)	E27
Mercury content	1.8 mg
Mercury-free	No

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

ILCOS	FBT-23/65/1B-220/240-E27
Order reference	DSTAR 23W/865 2


Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	176.00 mm
Height	52,0 mm
Width	52,0 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
- Not for use with external dimmers or electronic switches.

DOWNLOAD DATA

Photometric and lighting design files		Document name
	Spectral power distribution	349641_FL_865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300796147	Folding box 1	52 mm x 52 mm x 178 mm	0.11 g	0.48 dm ³
4058075011250	Shipping box 20	263 mm x 210 mm x 194 mm	2164.00 g	10.71 dm ³
4008321873620	Shipping box 20	268 mm x 216 mm x 193 mm	2.46 g	11.17 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.