

PRODUCT DATASHEET DST STICK 14 W/4000 K 220...240 V E27

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

Product benefits

- Fast return on investment
- $-\,$ Up to 80 % less energy consumption compared with ordinary light bulbs

Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220240 V
Nominal current	140 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	≥ 0.55

Photometrical data

Luminous flux	800 lm
Luminous efficacy	58 lm/W
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840

Light technical data

Starting time	≤ 0.3 s
---------------	---------

Dimensions & Weight

Overall length	135.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	60.00 g

Lifespan

Number of quitobing quales	≥10000
Number of switching cycles	210000

Additional product data

Base (standard designation)	E27
Mercury content	2.0 mg
Mercury-free	No

Country-specific categorizations

Order reference	DSTAR 14W/840 2

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	135.00 mm
Height	41.00 mm
Width	41.00 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
- Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899449572	Folding box	43 mm x 43 mm x 140 mm	77.00 g	0.26 dm ³
4058075076754	Bundle 10	215 mm x 86 mm x 139 mm	772.00 g	2.57 dm ³
4058075076761	Shipping box 10	226 mm x 95 mm x 156 mm	873.00 g	3.35 dm ³
4052899449589	Shipping box 10	226 mm x 95 mm x 156 mm	871.00 g	3.35 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.