

PRODUCT DATASHEET DULUX D 18 W/2700 K G24d-2

OSRAM DULUX® D | CFLni, 2 tubes, with 2-pin base for CCG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



TECHNICAL DATA

Electrical data

Nominal wattage	18 W
Construction wattage	18.00 W

Photometrical data

Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827

Dimensions & Weight

Overall length	153.00 mm
Diameter	11.00 mm
Product weight	45.76 g

Additional product data

Base (standard designation)	G24d-2
Mercury content	2.5 mg

Capabilities

Dimmable	No

Country-specific categorizations

<u> </u>		
()rder	reference	

DULUX D 18W/827

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24d-2
Length	153.00 mm
Height	11.00 mm
Width	11.00 mm

EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830852	Folding box 1	36 mm x 36 mm x 160 mm	62.80 g	0.21 dm ³
4058075497955	Shipping box 50	368 mm x 184 mm x 175 mm	3080.00 g	11.85 dm ³
4008321830869	Shipping box 10	187 mm x 81 mm x 175 mm	703.00 g	2.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.