

PRODUCT DATASHEET DULUX S 7 W 4000 K G23

OSRAM DULUX® S | Short CFLni, with 2-pin base for CCG operation



Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



TECHNICAL DATA

Electrical data

Nominal wattage	7 W
Construction wattage	7.00 W

Photometrical data

Luminous flux	400 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥ 80
Light color	840

Dimensions & Weight

Overall length	134.50 mm
Diameter	12.00 mm
Product weight	25.9 g

Additional product data

Base (standard designation)	G23
Mercury content	2.5 mg

Capabilities

Country-specific categorizations

Order refere	nce	DULUX S 7W/840
--------------	-----	----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G23
Length	137.00 mm
Height	12.00 mm
Width	12.00 mm

EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321664273	Folding box 1	36 mm x 23 mm x 139 mm	36.90 g	0.12 dm ³
4008321664280	Shipping box 10	190 mm x 53 mm x 152 mm	413.00 g	1.53 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.