

# PRODUCT DATASHEET DULUX S/E 7 W 4000 K 2G7

OSRAM DULUX® S/E | Short CFLni, with 4-pin base for ECG operation



## Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

#### **Product benefits**

- Extremly economical
- Good quality of light
- Improved maintenance
- Low power consumption (7 W, 9 W, 11 W)
- Long service life
- Extremely low profile

## Product features

- Short and compact pin-base lamps with single-turn tubes
- Single-ended four-pin plug-in 2G7 base
- Operates on battery, solar and AC power with suitable electronic control gear
- Not dimmable



## TECHNICAL DATA

## Electrical data

Nominal wattage	7 W
Construction wattage	7.10 W

### Photometrical data

Luminous flux	400 lm
Luminous flux at 25 °C	400 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	8090
Light color	840
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.81
Rated LLMF at 6,000 h	0.80
Rated LLMF at 8,000 h	0.76
Rated lamp efficacy (standard co.)	56 lm/W

# Dimensions & Weight

Overall length	112.00 mm
Diameter	12.00 mm
Maximum diameter	11 mm
Product weight	20.5 g

# Temperatures & operating conditions

	25.0 °C
--	---------

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	HF

# Additional product data

Base (standard designation)	2G7

Mercury content	1.3 mg
-----------------	--------

## Capabilities

Suitable for indoor	Yes
Dimmable	No

## Certificates & Standards

Energy efficiency class	А
Energy consumption	7.81 kWh/1000h

## Country-specific categorizations

ILCOS	FSD-7/40/1B-E-2G7
Order reference	DULUX S/E 7W/84

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	2G7
Length	114.00 mm
Height	12.00 mm
Width	12.00 mm

### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

### Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321583574	Folding box 1	38 mm x 22 mm x 127 mm	27.50 g	0.11 dm <sup>3</sup>
4008321583581	Shipping box 50	240 mm x 205 mm x 149 mm	1568.00 g	7.33 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.