

PRODUCT DATASHEET DULUX L 55 W/830 2G11

OSRAM DULUX® L LUMILUX® | CFLni, with 4-pin 2G11 base for ECG/CCG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Less than half as long as tubular fluorescent lamps

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Dimmable (1...100 % with QUICKTRONIC® QTi DALI/DIM)
- Good color rendering index



TECHNICAL DATA

Electrical data

Nominal wattage	55 W
Construction wattage	55.00 W
Nominal voltage	101 V

Photometrical data

Luminous flux at 25 °C	4800 lm
Color temperature	3000 K
Color rendering index Ra	> 80
Light color	830

Dimensions & Weight



Overall length	535.00 mm
Diameter	17.50 mm
Product weight	130.00 g

Additional product data

Base (standard designation)	2G11
Mercury content	3.0 mg

Country-specific categorizations

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	2G11
Length	535.00 mm
Height	17.50 mm
Width	17.50 mm

EQUIPMENT / ACCESSORIES

- Suitable for standard control gears and starters
- Suitable for operation on electronic and conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899318489	Folding box 1	46 mm x 26 mm x 562 mm	181.00 g	0.67 dm ³
4052899318496	Shipping box 25	572 mm x 241 mm x 147 mm	4841.00 g	20.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For more information on the system guarantee and the terms and conditions of the guarantee visit www.ledvance.com/system-guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.