

# PRODUCT DATASHEET NAV-T SUPER 150 W E40

VIALOX® NAV®-T SUPER 4Y® 50...400 W | High-pressure sodium vapor lamps for open and enclosed luminaires



#### Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

## Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- $-\,$  Energy savings of up to 50 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs

#### **Product features**

- Lamp survival factor: 95 % after 16,000 h burning time
- Lamp maintenance factor: ≥ 80 % after 16,000 h burning time (according to DIN 13201)
- Service lifetime: 4 years (at approx. 11 h/day)
- Dimmable on conventional control gears and electronic control gears

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	150 W
Construction wattage	150.00 W
PFC capacitor at 50 Hz	20 μF

# Photometrical data

Luminous flux	17500 lm
Luminous efficacy	112 lm/W
Color temperature	2000 K
Color rendering index Ra	≤ 25
Light color	220

# Dimensions & Weight

Overall length	210.00 mm
Light center length (LCL)	132,0 mm
Diameter	47 mm
Product weight	151.00 g

# Additional product data

Base (standard designation)	E40
Mercury content	3.0 mg
Design / version	Clear

# Country-specific categorizations

ILCOS	ST-150/20/40-H-E40-47/210
Order reference	NAV-T 150W SUPE

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E40
Length	210.00 mm
Height	47 mm
Width	47 mm

# Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Protect from spray water.

## DOWNLOAD DATA

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321806185	Sleeve 1	51 mm x 51 mm x 260 mm	178.00 g	0.68 dm <sup>3</sup>
4008321806192	Shipping box 12	222 mm x 171 mm x 299 mm	2075.00 g	11.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.