

## PRODUCT DATASHEET

### NAV-T 400 W E40

VIALOX® NAV®-T | High-pressure sodium vapor lamps for open and enclosed luminaires



#### Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High luminous efficacy

#### Product features

- Service lifetime: 3 years (at approx. 11 h/day)



## TECHNICAL DATA

### Electrical data

Nominal wattage	400 W
Nominal voltage	100 V
Ignition voltage	3.3/5.0 kVp <sup>1)</sup>
Nominal current	4.6 A

<sup>1)</sup> Minimum / Maximum

### Photometrical data

Luminous flux	48000 lm
Luminous efficacy	120 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.97
Rated LLMF at 4,000 h	0.96
Rated LLMF at 6,000 h	0.95
Rated LLMF at 8,000 h	0.94
Rated LLMF at 12,000 h	0.92
Rated LLMF at 16,000 h	0.91
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (standard co.)	122 lm/W
UV protection	No

### Dimensions & Weight

Overall length	285.00 mm
Length	285.00 mm
Light center length (LCL)	175,0 mm
Diameter	47 mm
Product weight	191.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.85
Lifespan B10	16000 h
Lifespan B5	12000 h
Lifespan B50	28000 h
Operation mode LLMF/LSF	50 Hz

#### Additional product data

Base (standard designation)	E40
Mercury content	19.9 mg
Mercury-free	No
Design / version	Clear
Product remark	Phased out in the EU as non ErP compliant according to EU directive 245/2009

#### Capabilities

Dimmable	Yes
Burning position	Any
Enclosed luminaire required	No

#### Certificates & Standards

Energy efficiency class	A+
Energy consumption	431.20 kWh/1000h

#### Country-specific categorizations

ILCOS	ST-400-H/E/SL-E40-47/285
Order reference	NAV-T 400W E40

#### Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300864044	Sleeve 1	52 mm x 52 mm x 325 mm	223.00 g	0.88 dm <sup>3</sup>
4050300864051	Shipping box 12	222 mm x 171 mm x 374 mm	2559.00 g	14.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.