

PRODUCT DATASHEET

NAV-T 150 W E40

VIALOX® NAV®-T | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- High luminous efficacy

Product features

- Service lifetime: 3 years (at approx. 11 h/day)

TECHNICAL DATA

Electrical data

Nominal wattage	150 W
Nominal voltage	100 V
Nominal current	1.8 A

Photometrical data

Luminous flux	15000 lm
Luminous efficacy	100 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.97
Rated LLMF at 4,000 h	0.96
Rated LLMF at 6,000 h	0.95
Rated LLMF at 8,000 h	0.94
Rated LLMF at 12,000 h	0.92
Rated LLMF at 16,000 h	0.91
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (standard co.)	100 lm/W

Dimensions & Weight

Overall length	210.00 mm
Length	210.00 mm
Diameter	47.00 mm
Product weight	154.00 g

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.85
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	E40
Mercury content	15.9 mg
Product remark	Phased out in the EU as non ErP compliant according to EU directive 245/2009

Certificates & Standards

Energy efficiency class	A+
Energy consumption	165.00 kWh/1000h

Country-specific categorizations

Order reference	NAV-T 150W E40
-----------------	----------------

Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300864006	Sleeve 1	51 mm x 51 mm x 260 mm	181.00 g	0.68 dm ³
4050300864013	Shipping box 12	222 mm x 171 mm x 299 mm	2111.00 g	11.35 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.