

# PRODUCT DATASHEET HE SL 21 W/865

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






# TECHNICAL DATA

# Electrical data

Nominal wattage	21 W
Construction wattage	20.60 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	85

# Photometrical data

Luminous flux	1750 lm
Luminous efficacy	83 lm/W
Luminous flux at 25 °C	1750 lm
Luminous flux at 35 °C	2000 lm
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	85



# Dimensions & Weight

Overall length	849.00 mm
Length with base excl. base pins/connection	849,00 mm

16,0 mm
16 mm
16 mm
65.00 g
35.0 °C
0.99
0.99
0.99
0.99
0.99
0.90
0.50
HF
G5
1.2 mg
Yes
A+
22.66 kWh/1000h
22.66 kWh/1000h
22.66 kWh/1000h  HE 21W/865 SL
HE 21W/865 SL
HE 21W/865 SL G5

### DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349641_FL_865

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321335524	Sleeve 1	863 mm x 18 mm x 18 mm	80.00 g	0.28 dm <sup>3</sup>
4052899046764	Shipping box 20	891 mm x 104 mm x 88 mm	2283.00 g	8.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.