

# PRODUCT DATASHEET L 30 W/765

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



### TECHNICAL DATA

#### Electrical data

Nominal wattage	30 W	
Construction wattage	30.00 W	
Nominal voltage	96 V	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

# Photometrical data

Luminous flux	1900 lm	
Luminous efficacy	63 lm/W	
Luminous flux at 25 °C	1900 lm	
Light color (designation)	Cool Daylight	
Color temperature	6500 K	
Color rendering index Ra 7079		
Light color	765	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

# Dimensions & Weight

Overall length	894.60 mm
Length with base excl. base pins/connection	895,00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	137.00 g

# Lifespan

Service life	5000 h
--------------	--------

## Additional product data

Base (standard designation)	G13
Mercury content	9.0 mg

# Country-specific categorizations

ILCOS	FD-30/765-E-G13-26/895
Order reference	L 30W/765 BASIC

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13

Length	895.00 mm
Height	26.00 mm
Width	26.00 mm

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300745268	Sleeve 1	910 mm x 29 mm x 29 mm	0.15 g	0.77 dm <sup>3</sup>
4050300745275	Shipping box 25	943 mm x 151 mm x 153 mm	3.91 g	21.79 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.