

PRODUCT DATASHEET L 36 W/640

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



TECHNICAL DATA

Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	103 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	2850 lm	
Luminous efficacy	79 lm/W	
Luminous flux at 25 °C	2850 lm	
Color temperature	4000 K	
Light color	40	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

Dimensions & Weight

Overall length	1199.40 mm
Length with base excl. base pins/connection	1200 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	165.00 g

Lifespan

Service life	5000 h
Service life	3000 H

Additional product data

Base (standard designation)	G13
Mercury content	9.0 mg

Country-specific categorizations

ILCOS	FD-36/640-E-G13-26/1200
Order reference	L 36W/640 BASIC

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13	
Length	1200.00 mm	
Height	26.00 mm	

Width	26.00 mm
-------	----------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4006584043880	Sleeve 1	1,215 mm x 29 mm x 29 mm	198.00 g	1.02 dm ³
4006584043897	Shipping box 25	1,253 mm x 151 mm x 153 mm	5251.00 g	28.95 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.