

# PRODUCT DATASHEET LED PRO Phase Cut Dimmable 20/220... 240/500

LED PRO Phase-cut Dimmable CC Driver | Compact constant current LED driver with phase-cut dimming interface



#### Areas of application

- For indoor SELV installations
- Suitable for downlights, spotlights, LED panels, etc.
- Offices, shopping centers, hospitals, restaurants, hotels

#### Product benefits

- Compatible with many common leading-edge and trailing-edge phase dimmers
- High flexibility due to adjustable output currents via dip switch
- Small housing for flexible luminaire designs

#### **Product features**

- Safety extra-low voltage (SELV) driver
- Built-in or independent installation with optional Cable Clamp Kit possible
- Available in 12 W, 20 W, 30 W
- Low ripple current < 5%</li>
- Lifetime: up to 50,000 h (at max. tc temperature)
- Safety according to IEC 61347-1, IEC 61347-2-13
- EMC immunity according to EN 55015, IEC 61547, IEC 61000

# TECHNICAL DATA

# Electrical data

Nominal wattage	20.00 W
Nominal voltage	220240 V
Nominal output voltage	2542 V
Input voltage AC	220-240 V
Nominal current	0,11 A
Output current tolerance	+/- 5 %
Output ripple current (100 Hz)	≤ 5 %
Mains frequency	50/60 Hz
Total harmonic distortion	< 15 % <sup>1)</sup>
Power factor λ	≥ 0.95 <sup>1)</sup>
ECG efficiency	84 % 1)
Surge capability (L-N)	1 kV

<sup>1)</sup> At full load

# Dimensions & Weight



Length	97.00 mm
Width	40.00 mm
Height	27.00 mm
Cable cross-section, input side	0.751.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Product weight	93.00 g

### Colors & materials

Body material	Polycarbonate (PC)
Temperatures & operating conditions	

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	75 °C

# Capabilities

Dimmable	Yes
----------	-----

Dimming interface	Phase Cut
Overload protection	Yes
Short-circuit protection	Yes

#### Certificates & Standards

Standards		CB / EMC / ROHS
Protection	class	П
Type of pr	otection	IP20

# Accessories Optional

Product image	Product name	EAN	
		4058075550551	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854013140	Unpacked 1	36 mm x 26 mm x 89 mm	84.00 g	0.08 dm <sup>3</sup>
4099854013157	Shipping box 40	218 mm x 212 mm x 152 mm	4412.00 g	7.02 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.