

# PRODUCT DATASHEET

## LM RETROFIT C ECO 24 W/865

LEDVANCE Retrofit Circular Module | LED Modules with integrated optics and driver



---

### Areas of application

- Hallways, corridors

---

### Product benefits

- Compact, lightweight
- Self-adhesive backing for simple installation

---

### Product features

- LED light engine with integrated driver
- Color rendering index  $R_a: > 80$
- Input voltage: 220...240 V<sub>AC</sub>
- LED replacement for luminaires that use traditional circular fluorescent lamps

## TECHNICAL DATA

### Electrical data

|                        |             |
|------------------------|-------------|
| Nominal wattage        | 24.00 W     |
| Construction wattage   | 24.00 W     |
| Nominal voltage        | 220...240 V |
| Type of current        | AC          |
| Power factor $\lambda$ | > 0.50      |

### Photometrical data

|                           |          |
|---------------------------|----------|
| Luminous efficacy         | 90 lm/W  |
| Luminous flux             | 2200 lm  |
| Color temperature         | 6500 K   |
| Color rendering index Ra  | 80       |
| Light color (designation) | Daylight |

### Light technical data

|            |       |
|------------|-------|
| Beam angle | 160 ° |
|------------|-------|

### Dimensions & Weight



|                |           |
|----------------|-----------|
| Length         | 228.00 mm |
| Width          | 228.00 mm |
| Height         | 24.00 mm  |
| Product weight | 131.00 g  |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+45 °C |
| Maximum temperature at tc test point | 75 °C        |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

## LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -25...+85 °C |
|------------------------------|--------------|

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                 |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075148710 | Folding box<br>1             | 236 mm x 30 mm x 236 mm              | 182.00 g     | 1.67 dm <sup>3</sup>   |
| 4058075148727 | Shipping box<br>10           | 326 mm x 251 mm x 257 mm             | 2166.00 g    | 21.03 dm <sup>3</sup>  |
| 4058075148734 | Shipping box<br>60           | 795 mm x 355 mm x 545 mm             | 14786.00 g   | 153.81 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.