

PRODUCT DATASHEET

LED Value Slim Downlight 18 W/6500 K

LED VALUE SLIM DOWNLIGHT | Flat downlight luminaires



Areas of application

- Corridors, entrance areas
- Foyers
- Elevators
- Retail

Product benefits

- Die-cast aluminum housing for improved heat dissipation
- No light can escape at the back of the luminaires thanks a special cover
- Elegant design

Product features

- Product color: white
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- High color consistency: ≤ 6 SDCM
- Luminaire efficacy: up to 89 lm/W
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h
- Protection class: II
- Uniform illumination



TECHNICAL DATA

Electrical data

Nominal wattage	18.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.50
Protection class	II

Photometrical data

Luminous flux	1600 lm
Luminous efficacy	89 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	≤ 6 sdc _m
Beam angle	120 °

Dimensions & Weight

Length	225.00 mm
Width	225.00 mm
Height	20.00 mm
Product weight	400.00 g

LDVAL SLIM downlight SQ 205
18W

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum

Cover material	Plastic
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting length	205,0 mm
Mounting width	205,0 mm
Replaceable light source	No

Lifespan


Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LDVAL SLIMDL SQ 205 18W 865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075314214	Folding box 1	265 mm x 47 mm x 230 mm	527.00 g	2.86 dm ³
4058075314221	Shipping box 20	478 mm x 276 mm x 482 mm	11307.00 g	63.59 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.