


# PRODUCT DATASHEET

## LED WALL WASHER 36 W 4000 K 45 ° 500 mm

LED WALL WASHER | LED floodlight luminaires

### Areas of application

- Architectural lighting
- Facade lighting



### Product benefits

- Prewired plug connector (male/female) for easy installation
- High quality lens made of polycarbonate (PC), secondary optics with tempered glass cover
- Flexibility and convenience in use thanks to adjustable mounting bracket

### Product features

- Extruded aluminum housing and die-cast aluminum end caps
- Available in two lengths: 500 mm and 1000 mm
- Available with color temperature: 3,000 K, 4,000 K
- Input voltage: 24 V<sub>DC</sub>
- Initial color consistency: < 5 SDCM
- Luminaire efficacy: up to 80 lm/W
- Color rendering index R<sub>a</sub>: ≥ 80



- Type of protection: IP66
- Impact resistance: IK05
- Lifetime (L70/B50): up to 30,000 h
- With CQC certificate
- Certificate: CB

TECHNICAL DATA

Electrical data


Nominal wattage	36.00 W
Nominal voltage	24 V
Nominal current	1500.000 mA
Protection class	III

Photometrical data

Luminous flux	2880 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80
Standard deviation of color matching	≤5 sdcn
Beam angle	45 °

Dimensions & Weight

Length	500.00 mm
Width	70.00 mm
Height	78.70 mm
Product weight	1450.00 g
Cable length	200 mm



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Glass Aluminum
Cover material	CLEAR GLASS

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+70 °C
Type of connection	Plug, quick disconnect
Type of protection	IP66
Protection class IK (shock resistance)	IK05
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	30000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075334632	Folding box 1	510 mm x 85 mm x 75 mm	1584.00 g	3.25 dm <sup>3</sup>
4058075334649	Shipping box 4	530 mm x 185 mm x 180 mm	6838.00 g	17.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.