

PRODUCT DATASHEET LED WALL WASHER 24 W 45 ° 1000 mm RGB

LED WALLWASHER RGB | LED outdoor luminaires with RGB



Areas of application

- Architectural lighting
- Facade lighting

Product benefits

- High quality lens made of polycarbonate (PC), secondary optics with tempered glass cover
- Flexibility and convenience in use thanks to adjustable mounting bracket

Product features

- Extruded aluminum housing and die-cast aluminum end caps
- Available in two lengths: 500 mm and 1000 mm
- RGB color control
- Type of protection: IP66
- Impact resistance: IK05
- Lifetime (L70/B50): up to 30,000 h
- With CQC certificate
- Certificate: CB



TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Nominal voltage	24 V
Nominal current	1000.000 mA
Protection class	Ш

Photometrical data

Luminous flux	432 lm
Luminous efficacy	18 lm/W
Light color (designation)	RGB
Standard deviation of color matching	≤5 sdcm
Beam angle	45 °

Dimensions & Weight

Length	1000.00 mm
Width	38.00 mm
Height	56.00 mm
Product weight	1450.00 g
Cable length	200 mm



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Glass Aluminum
Cover material	CLEAR GLASS
Mercury content	0.0 mg

Application & Mounting

A - + +	00 . 50 00
Ambient temperature range	-20+50 °C
Temperature range at storage	-20+70 °C
Type of connection	Plug, quick disconnect
Type of protection	IP66
Protection class IK (shock resistance)	IK05
Dimmable	Yes
Type of dimming	DMX
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075335066	Folding box	1,010 mm x 55 mm x 50 mm	1581.00 g	2.78 dm ³
4058075335073	Shipping box 9	1,030 mm x 185 mm x 180 mm	15075.00 g	34.30 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.